


SOJ HIGH-FREQUENCY CRYSTAL OSCILLATOR

SG-615 series

- High-density mounting-type SMD.
- A general-purpose SMD with heat-resisting cylindrical AT-cut crystal unit and allowing almost the same soldering temperature as SMD IC.
- Cylindrical AT crystal unit built-in, thus assuring high reliability.
- Provided with output enable function.
- Low current consumption.




Specifications (characteristics)

Item	Symbol	SG-615P	SG-615PTJ	SG-615PH	Remarks	
		Specifications				
Output frequency range	f_0	1.0250 MHz to 26.0000 MHz	26.0001 MHz to 66.6667 MHz			
Power source voltage	Max. supply voltage	V_{DD-GND}	-0.3V to +7.0V			
	Operating voltage	V_{DD}	5.0V±0.5V			
Temperature range	Storage temperature	T_{STG}	-55°C to +125°C		Stored as bare product after unpacking	
	Operating temperature	T_{OPR}	-10°C to 70°C (-40°C to 85°C)			
Soldering condition	T_{SOL}	Twice at under 260°C within 10 sec. or under 230°C within 3 min.			55MHz max. (-40°C to +85°C)	
Frequency stability	$\Delta f/f_0$	B: ±50ppm C: ±100ppm			B type is possible up to 55 MHz	
Current consumption	I_{OP}	23mA max.	35mA max.		No load condition	
Duty	C-MOS level	t_w/t	40% to 60%	—	40% to 60%	C-MOS load: 1/2V _{DD}
	TTL level		45% to 55%		—	TTL load: 1.4V
Output voltage	V_{OH}	$V_{DD} - 0.4V$ min.	2.4V min.	$V_{DD} - 0.4V$ min.		
	(I_{OH})	-400µA				
	V_{OL}	0.4V max.				
	(I_{OL})	16mA	8mA	4mA		
Output load condition (fan out)	C-MOS	C_L	50pF max.	—	50pF max.	
	TTL	N	10TTL max.	5TTL max.	—	
Output enable/disable input voltage	V_{IH}	2.0V min.	3.5V min.	2.0V min.	$I_{IH} = 1\mu A$ max. (OE= V_{DD})	
	V_{IL}	0.8V max.	1.5V max.	0.8V max.	$I_{IL} = -100\mu A$ min. (OE=GND) $I_{IL} = -500\mu A$ min. (OE=GND) PTJ	
Output disable current	I_{OE}	12mA max.	28mA max.	20mA max.	OE=GND	
Output rise time	C-MOS level	t_{TLH}	—	7ns max.	C-MOS load: 20%→80% V_{DD}	
	TTL level		8ns max.	5ns max.	—	TTL load: 0.4V→2.4V
Output fall time	C-MOS level	t_{THL}	—	7ns max.	C-MOS load: 80%→20% V_{DD}	
	TTL level		8ns max.	5ns max.	—	TTL load: 2.4V→0.4V
Oscillation start up time	t_{OSC}	4ms max.	10ms max.		Time at 4.5V to be 0 sec.	
Aging	f_a	±5ppm/year max.			$T_a = 25^\circ C, V_{DD} = 5V$, first year	
Shock resistance	S.R.	±20ppm max.			Three drops on a hard board from 75 cm or excitation test with 3000G x 0.3ms x 1/2sine wave in 3 directions	

Note: • Unless otherwise stated, characteristics (specifications) shown in the above table are based on the rated operating temperature and voltage condition.
• External by-pass capacitor is recommended.

External dimensions

(Unit: mm)



Recommended soldering pattern

(Unit: mm)

